




# Wall sandwich panels EMW-Lite-Mw 1130



## Wall sandwich panels EMW-Lite Mw 1130 data sheet

Type of insulation (core)	Mineral wool						
Insulant density [kg/m <sup>3</sup> ]	85 ±10%						
Panel thickness H [mm]	100	120	140	150	160	180	200
Weight 1 m <sup>2</sup> (sheeting 0.5/0.5) [kg]	16.6	18.3	20.0	20.9	21.7	23.4	25.1
Panel length [mm]	2000 - 10000						
Modular width [mm]	1130 ±2   on demand 1000 or 1050 ±2 mm						
External steel sheeting thickness [mm]	0.5 / 0.6						
Internal steel sheeting thickness [mm]	0.5 / 0.6						
Thermal transmittance (U-value) [W/m <sup>2</sup> K]	0.38	0.32	0.27	0.25	0.24	0.21	0.19
Reaction to fire	A2-s1, d0						
Sound reduction index Rw [dB]	33				31		34
Coatings	- polyester, 25 µm (standard coating)						
Certificates	EN 14509						

# Wall sandwich panels EMW-Lite-Mw 1130



# Wall sandwich panels EMW-Lite Mw 1130

## Colours

### Standard RAL colours of the external sheeting PE 25 µm



RAL 1015



RAL 7035



RAL 9001



RAL 9002



RAL 9006




RAL 9010

### Nonstandard RAL colours of the external sheeting PE 25 µm



RAL 1002



RAL 1021



RAL 3000



RAL 3011



RAL 3016



RAL 5010



RAL 5012



RAL 6029



RAL 7016



RAL 7024



RAL 8017




RAL 9007


### RAL colours of the external sheeting PE 25 µm on demand




RAL 1018



RAL 6011



RAL 7040



RAL 8004

### Standard RAL colours of the internal sheeting PE 25 µm



RAL 9002



RAL 9010

### Internal sheeting . FoodSafe



White